

<sup>(12)</sup> UK Patent Application <sup>(19)</sup>GB <sup>(11)</sup> 2 058 505 A

- (21) Application No 8031114
- (22) Date of filing 9 Jun 1978  
Date lodged 25 Sep 1980
- (30) Priority data
- (31) 813137  
813202  
813198
- (32) 5 Jul 1977  
5 Jul 1977  
29 Jul 1977
- (33) United States of America  
(US)
- (43) Application published  
8 Apr 1981
- (51) INT CL<sup>3</sup>  
H03D 7/12 H04B 1/28
- (52) Domestic classification  
H3T 2B9 2T3F 2T4 3V FX  
H3Q BMW
- (56) Documents cited  
IEEE Transactions On  
Electron Devices Vol. ED,  
25 No. 6 June 1978  
"Noise Temperature In  
GaAs EPI-Layer For Fet's  
pp. 596—599 (see  
especially p. 598 line 8  
reference to mixer)
- (58) Field of search  
H1K  
H3T


- (60) Derived from Application  
No 26602/78 under  
Section 15(4) of the  
Patents Act 1977
- (71) Applicants  
Texas Instruments  
Incorporated, 13500  
North Central  
Expressway, Dallas,  
Texas,  
United States of America
- (72) inventor  
Darrell Lee Ash
- (74) Agents  
Abel & Inray,  
Northumberland House,  
303—308 High Holborn,  
London WC1V 7LH

- (54) Channel selector for television receiver**

- (57) A channel selector for a television receiver having a fixed broad band RF section 12, 13, 16 for passing a plurality of channels, and a MESFET mixer 20, 67 for converting a selected channel in the band of signals from


the RF section to a high intermediate frequency substantially greater than 45 MHz. The high intermediate frequency is disclosed as 300—400 MHz and is selected by an acoustic surface wave filter 28. The intermediate frequency is chosen so that twice the intermediate frequency exceeds the bandwidth of the RF section. The signals at the high intermediate frequency are converted at 32 to a low intermediate frequency (45 MHz) for amplification.

**This print embodies corrections made under Section 117(1) of the Patents Act 1977. The drawings originally filed were informal and the print here reproduced is taken from a later filed formal copy. The date of filing shown above is that provisionally accorded to the application in accordance with the provisions of Section 15(4) of the Patents Act 1977, and is subject to ratification or amendment at a later stage of the application proceedings.**




**Fig. 1**



# GB 2 058 505 A







2/16



3/16



4/16








Fig. 9a




Fig. 9b







Fig. 9c




**Fig. 9d****Fig. 9e**




2058505



8/16

**Fig. 11a**



**Fig. 11b**





10/16

Fig. IIe






Fig. II f



$$|X_L| = R \sin \theta$$

$$|X_C| = \frac{R \sin \theta}{(1 - \cos \theta)}$$

Fig. IIg








Fig. IIh




12/16




**Fig. 14b.**


**Fig. 15**




**Fig. 16**




**Fig. 17**



**Fig. 18**



**Fig. 19**






Fig. 20






Fig. 21

## SPECIFICATION Channel selector

### BACKGROUND OF THE INVENTION

This invention relates to electronic devices for receiving a plurality of radiated electromagnetic signals, filtering a selectable channel of frequencies from the received signals, and demodulating the signals of the selected filtered channel. More particularly, the invention relates to television receivers.

Television receivers of the prior art include a radio frequency (RF) section and an intermediate frequency (IF) section. The RF section includes RF filters which are tuned to coarsely filter a band of channels centered about a manually selected channel. The output of the RF filter coupled to the input of an RF amplifier. Typically, total gain through the RF section is at least 20 dB to 30 dB. This gain increases the amplitude of signals within the selected channel and additionally makes the noise figure of the system essentially independent of subsequent elements in the receiver. The output of the RF amplifier coupled to one input of a mixer, while a second input of the mixer receives mixing signals of a selectable frequency. The selectable frequency is generated such that the selected channel is frequency shifted to approximately 45 MHz. The output of the mixer couples to a channel selection filter which provides a relatively high impedance path for frequencies outside of the selected channel, and a relatively low impedance path for signals inside the selected channel. Signals at the output of the channel selection filter are therefore primarily comprised of frequencies within the selected channel.

Each television channel contains audio information, video information, and frame synchronizing information. The output of the channel selection filter coupled to an audio demodulator which separates the audio information from the selected channel; and the output of the audio demodulator couples to a speaker which generates audible sounds. Similarly, the output of the channel selection filter couples to a video processing unit which separates the video and frame synchronizing information from the selected channel; and the output of the video processor couples to a picture tube which converts the video and frame synchronizing information to pictures.

As described above, a basic function which all television receivers perform is to frequency shift the selected channel from an RF frequency to a predetermined IF frequency by a mixing device. This mixing operation has been performed in the past by a variety of nonlinear devices. These devices include vacuum tubes, diodes, MOSFET transistors, and bipolar transistors. However, the prior art mixers also generate output terms which are proportional to their inputs cubed or raised to higher order odd powers. In a television receiver, these odd power terms may generate interfering signals in the desired channel. For example, such interfering signals are generated when signals are

present in channels on one side of the selected channel which are one and two channels removed from the selected channel. This phenomena is known as intermodulation distortion. Similarly, the cubic terms and higher order odd power terms generate interfering signals in the desired channel when a carrier with amplitude modulation is present in any one of the undesired channels. This phenomena is known as cross modulation distortion. The frequencies which are generated in a desired channel as a result of intermodulation distortion or cross modulation distortion cannot be separated from the information signals lying therein. Thus, as the magnitude of the interfering frequencies increases, perceptible picture distortion or sound distortion occurs.

A principal advantage of the television receiver herein disclosed is that it has greatly reduced cross modulation and intermodulation distortion. This is accomplished to a large extent by means of a unique RF mixer. The mixer utilizes a MESFET transistor which has almost perfect square law current-voltage characteristics. Since the MESFET mixer has almost perfect square law characteristics. The mixer introduces extremely small distortion into the system. In particular, the MESFET mixer handles an interfering signal level of greater than +6 dBm on its output with less than 1% cross modulation distortion and -40 dB intermodulation distortion products.

The square law current-voltage characteristics of a MESFET transistor and their application to reduce intermodulation and cross modulation distortion in a television receiver is not taught by the prior art. In the past, MESFET devices were used primarily to achieve high speed operation. For example, they were utilized in pico-second digital switching circuits. See, for example, a paper by Cahen et al entitled "A Subnanosecond Switching Circuit" which was presented at the IEEE International Solid State Circuits Conference on February 14, 1974 at Orsay, France. See also, for example, a paper entitled "X and KU Band Amplifiers with GaAs Schottky Barrier Field Effect Transistors" by Weiner Baechtold in the IEEE Journal of Solid State Circuits Volume, SC-8, No. 1, February 1973. High speed digital switching is combined with high speed linear amplification in a high speed pulse amplitude modulation device that is described in the paper entitled "Performance of Dual Gate GaAs MESFETS as Gain Controlled Low Noise Amplifiers and High Speed Modulators" by Liechti in the IEEE Transactions on Microwave Theory and Techniques Vol. MIT-23, No. 6, June 1975. However, all of the devices in the above cited references only utilize MESFETS for high speed.

The television receiver herein disclosed is also novel in that it includes a unique combination of surface wave device technology with MESFET device technology in the RF-IF section. A MESFET mixer provides frequency shifting while channel selectivity is provided by a single low loss surface acoustic wave bandpass filter. This filter has a sharp passband—stop band transition. For

example, signals 1.5 MHz above the sound carrier in the passband are attenuated by greater than 65 dB. Conversely, the filter has a low insertion loss for signals in the passband. The preferred embodiment is a unidirectional filter which has an inband insertion loss of less than 3.5 dB.

The SWD filter also has a high center frequency and a passband which is a small percentage of the center frequency. Thus, the SWD is readily implemented with piezoelectric material having a relatively low coefficient of coupling. Quartz has such a characteristic, and it is a preferred substrate material. By comparison, prior art television receivers employed SWD filters only at a much lower IF frequency of 45 MHz. Accordingly, their passband was a relatively large percentage of their center frequency and thus the devices needed piezoelectric material having a relatively large coefficient of coupling such as lithium niobate. Lithium niobate, however, has piezoelectric characteristics which are highly sensitive to temperature change in the 0°—70°C temperature range. As a result, they require temperature compensation circuitry. By comparison, the piezoelectric characteristics of quartz are relatively insensitive to temperature change in the 0°—70° temperature range; and thus no temperature compensation circuitry is required.

Prior art television receivers include RF tuned filters before the mixer to insure that image frequencies of the selected channel are sufficiently attenuated at the mixer input so as to not produce interfering mixer output signals. To accomplish this, the bandwidth of the tuned RF filters are only several channels wide, and the center frequency is adjusted to align with the selected channel. RF filters which pass all of the channels of the VHF and UHF band at one time cannot be utilized because image frequencies would destroy reception in the selected channel.

To demonstrate the above point, consider the following. VHF television channels exist from 55.25 MHz to 71.75 MHz, and from 177.25 MHz to 215.75 MHz; while UHF channels exist from 471.25 MHz to 889.5 MHz. Also, as is known in the art, the image frequencies of a selected channel lie at 2XIF above the selected channel. Thus, channel 6, for example, which is centered at 87.75 MHz, has an image frequency in a conventional television receiver at (87.75 + 90) MHz. This equals 177.75 MHz—which is within channel 7. Similarly, the picture carrier for channel 14 is 471 MHz; and thus its image frequency is 561 MHz—which is within channel 29. Accordingly, prior art receivers need an RF tuner before the mixer to filter image frequencies.

In the prior art, RF tuning is accomplished by varactor filters, mechanically variable capacitors, etc. However, these are both expensive and difficult to align. By comparison, the television receiver of the disclosed invention has no tuners in the RF section. In one preferred embodiment, a fixed bandpass filter is included which passes the

entire low VHF band, a second filter is included which passes the entire high VHF band, and a third filter is included which passes the entire UHF band. These fixed filters are simple in design and eliminate alignment problems. The disclosed invention also includes a mixer having an IF output frequency of between 300 MHz and 400 MHz. As a result, image frequencies of the selected channel are placed at least 600 MHz above the selected channel where they are easily rejected by the fixed bandpass RF filters.

The mixer output of the disclosed receiver couples to a channel selection filter which is implemented by an improved surface wave device. Prior art television receivers also used surface wave device channel selection filters. However, the SWD filter of the disclosed invention is an improvement from the prior art in that it is constructed on a relatively small substrate area. The area used by a SWD filter is proportional to its center frequency. Conventional receivers have an IF frequency of 45 MHz, and thus, the SWD's used therein require substantially more space.

Another novel aspect of the disclosed system is that the IF section includes two mixers at the output of the SWD filter for frequency shifting the selected channel back to baseband. The first IF mixer frequency shifts the selected channel to approximately 45 MHz. Most of the gain of the system is then added to the selected channel signals. The second IF mixer is utilized to synchronously detect signals in the selected channel. This architecture permits the described high IF system advantages to be achieved, without introducing high frequency feedback problems.

As previously described, prior art television receivers insert at least 20 to 30 dB of gain in the RF section to achieve a low system noise figure. System noise figure equals

$$NF_1 + \frac{NF_2 - 1}{G_1} + \frac{NF_3 - 1}{G_1 G_2} + \frac{NF_4 - 1}{G_1 G_2 G_3} + \dots$$

wherein  $NF_i$  and  $G_i$  are the noise figure and gain of the  $i$ th functional block in the system. Thus, inserting a large gain in the first functional blocks (i.e. the RF section) lowers system noise figure by making it independent of noise figure of subsequent circuitry.

The disclosed invention has a unique architecture which achieves low noise figure, low intermodulation distortion and low cross-modulation distortion simultaneously. In the preferred embodiment, the disclosed invention has a maximum gain in the channel selecting section which is less than 10 dB; that utilizes circuit elements therein which individually have low noise figures yield a low system noise figure, while the low gain allows RF and IF circuit elements to operate within their dynamic range without generating high odd order output terms.

The architecture of the disclosed invention is also novel in that it has two IF frequencies about which the system gain is selectively distributed. In

one preferred embodiment, a first mixer shifts the selected channel to about 330 MHz. The output of this mixer couples to the channel selection filter; and the output of the channel selection filter  
 5 couples to a second mixer which frequency shifts the filtered selected channel to a second IF frequency of approximately 45 MHz. Most of the gain of the system (approximately 60 dB) is inserted at the lower IF frequency after the  
 10 channel selection filter. Gain at the higher IF is small as pointed out above. As a result, several advantages of a high IF system—such as simplified filtering of image frequencies—are obtained, while feedback inherent in a high gain-high IF section is avoided.

The disclosed system is also simpler and potentially less expensive than prior art television receivers in that the low gain RF section makes feasible integration of a major portion of the receiver on a single semiconductor chip.  
 20 Incorporated in the disclosure are two differently organized RF—IF sections which are suitable for semiconductor chip integration.

#### SUMMARY OF THE INVENTION

25 A high-frequency channel selector for a television receiver having only fixed filters in the RF section is provided which includes at least one fixed filter having a predetermined passband and a high-frequency mixer. The antenna for the  
 30 television receiver receives radiated electromagnetic signals including, for example, a plurality of television channels. The fixed filters having inputs coupled to the antenna and filter fixed spectrums of television channels from the received signals. A preferred embodiment includes  
 35 one fixed filter to pass the entire low VHF spectrum, another fixed filter to pass the entire high VHF spectrum, and another fixed filter to pass the entire UHF spectrum. The mixer includes a metal semiconductor field effect transistor, i.e., MESFET, and has inputs coupled to  
 40 simultaneously receive one of the fixed spectrums of channels and mixing signals of a high selectable frequency. The high selectable frequency shifts selectable channels of the spectrum to a high intermediate frequency (IF) substantially greater than 45 MHz. The high IF in a preferred  
 45 embodiment is between 300 MHz—400 MHz. An acoustic surface wave device (SWD) filter is also included in a preferred embodiment. The SWD couples to the mixer output and filters the selectable channel at the high IF. The substrate of the SWD has a low coefficient of coupling, and in a preferred embodiment it is quartz.

#### 55 BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims; the invention itself, however, as well as other features and advantages thereof, may best be understood  
 60 by referring to the following detailed description of particular embodiments when read in reference to the accompanying drawings, wherein:

FIGURE 1 is a block diagram illustrating a

channel selector constructed according to the invention.

FIGURE 2 is a series of frequency diagrams illustrating signals at selected points on the channel selector of FIGURE 1.

FIGURE 3 is a timing diagram illustrating the operation of a phase locked loop within the channel selector of FIGURE 1.

FIGURE 4 is a set of graphs illustrating the amplitude of in-band and out-of-band signals at various points in the channel selector of FIGURE 1.

FIGURE 5 is a set of detailed circuit diagrams of RF filters within the channel selector of FIGURE 1.

FIGURE 6 is a detailed circuit diagram of a two-by-one switch within the channel selector of FIGURE 1.

FIGURE 7 is a detailed circuit diagram of an RF amplifier within the channel selector of FIGURE 1.

FIGURE 8 is a detailed circuit diagram of a MESFET mixer within the channel selector of FIGURE 1.

FIGURES 9a—9e illustrate the structural and operational characteristics of a MESFET transistor suitable for amplification in the MESFET mixer of FIGURE 8.

FIGURE 10 is a circuit diagram of a second two-by-one switch within the channel selector of FIGURE 1.

FIGURES 11a—11h are diagrams illustrating the structural and operational details of a surface wave device acoustic filter within the channel selector of FIGURE 1.

FIGURES 12a—12b are detailed circuit diagrams of a linear amplifier within the channel selector of FIGURE 1.

FIGURE 13 is a detailed circuit diagram of a mixer within the channel selector of FIGURE 1.

FIGURES 14a—14b are detailed circuit diagrams of a surface wave device oscillator within the channel selector of FIGURE 1.

FIGURE 15 is a detailed circuit diagram of a high gain linear amplifier within the channel selector of FIGURE 1.

FIGURE 16 is a detailed circuit diagram of a synchronous detector within the channel selector of FIGURE 1.

FIGURE 17 is a detailed circuit diagram of a L—C oscillator within the channel selector of FIGURE 1.

FIGURE 18 is a detailed circuit diagram of a phase detector, a ramp-generator, and a loop filter within the channel selector of FIGURE 1.

FIGURE 19 is a detailed circuit diagram of a voltage controlled oscillator within the channel selector of FIGURE 1.

FIGURE 20 is a block diagram of a television receiver which includes the channel selector of FIGURE 1.

FIGURE 21 is a block diagram of an alternative embodiment for the channel selector of FIGURE 1.

#### DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

Referring to FIGURE 1, the channel selecting portion of a television constructed according to

the invention is illustrated in block diagram form. The selector includes a VHF antenna 10 having an output coupled via a lead 11 to a fixed bandpass filter 12 and to another fixed bandpass filter 13.

5 Signals on lead 11 are herein designated  $S_1(f)$ . Filter 12 has a center frequency of 69 MHz and a 3 dB bandwidth of 34.6 MHz to thereby permit passage of the low VHF television channels. Similarly, filter 13 has a center frequency of 10 193 MHz and a 3 dB bandwidth of 44.5 MHz to provide filtering of the high VHF television channels. The output of filter 12 is coupled via a lead 14 to one of the inputs of a  $2 \times 1$  switch 15, while the output of filter 13 is coupled via a lead 16 15 to a second input of switch 15. Switch 15 operates to select either signals from filter 12 or filter 13. The filter-switch combination inserts approximately a 1 dB loss on signals in the passbands.

20 The output of switch 15 is coupled to an RF amplifier 17 via lead 18. Amplifier 17 has a variable gain which is controlled by signals on an AGC line 19. The maximum gain of amplifier 17 is approximately 4 dB. The noise figure of the 25 amplifier is approximately 3 dB.

The output of amplifier 17 couples to one input of a MESFET mixer 20 via a lead 21. Mixer 20 has a fixed gain of approximately 4 dB, and a noise figure of approximately 8 dB. A second input of 30 mixer 20 is coupled to a VHF voltage controlled oscillator 22 via a lead 23. Oscillator 22 generates local oscillator (LO) signals on lead 23 of a selectable frequency in the range 385—541 MHz. In response thereto, mixer 20 frequency shifts the 35 RF signals on lead 21 to a new IF frequency range. The frequency of the LO signals on lead 23 is selected such that the channel to be received is frequency shifted to a predetermined high IF of between 300 MHz to 400 MHz. In one 40 embodiment, this predetermined high IF is approximately 330 MHz. The frequency shifted signals are generated on a lead 24 and are designated  $S_2(f)$ .

Lead 24 couples to one input of a  $2 \times 1$  switch 45 25, while a second input of switch 25 is coupled via a lead 26 to receive frequency shifted UHF television channels. Switch 25 is identical in construction to switch 15. The circuitry for frequency shifting the UHF television channels, which is labeled as UHF RF SECTION, is similar in 50 construction to the VHF—RF section, and is described in detail infra.

The output of switch 25 is coupled to a surface wave device (SWD) filter 28 via a lead 27. Filter 55 28 has a passband which is shaped to pass only one of the television channels on lead 27. In particular, filter 28 passes the television channel at the predetermined high IF. The fixed RF filters in combination with the SWD filter provide 60 essentially all the filtering in the system. In a preferred embodiment, filter 28 is a three phase unidirectional filter which has a low insertion loss. Typically, the loss through filter 28 is less than 3.5 dB in the passband. Conversely, out of band 65 signals are greatly attenuated.

The output of filter 28 is coupled to an IF amplifier 29 via a lead 30. The signals on lead 30 are designated herein as  $S_3(f)$ . Amplifier 29 has a variable gain which is controlled by AGC signals on a lead 31. The maximum gain of amplifier 29 is approximately 30 dB. Thus, amplifier 29 is the first high gain element in the system. To this point, the gain of the system is characterized as being no larger than necessary to obtain the desired system noise figure. Noise figure for amplifier 29 is approximately 4 dB.

70 The output of amplifier 29 couples to a mixer 32 via a lead 33. A second input of mixer 32 is coupled via a lead 34 to the output of an oscillator 35. Oscillator 35 has a surface wave device resonator 36 as its frequency controlling element. In a preferred embodiment, resonator 36 and oscillator 35 operate to generate a mixing signal on lead 34 having a frequency of 285 MHz. The 80 285 MHz signal on lead 34 is mixed with the signal on lead 33 to thereby generate signals  $S_4(f)$  on the output of mixer 32. Signal  $S_4(f)$  is similar to signal  $S_3(f)$  except that it is shifted down in frequency by 285 MHz. Thus it has a picture 90 carrier at approximately 45 MHz.

Additional gain is added to the signal of the selected channel after it has been frequency shifted to the lower IF frequency of 45 MHz. Mixer 32 adds a fixed gain of +10 dB. And the output of 95 mixer 32 couples via a lead 37 to an IF amplifier 38 which has a maximum gain of +50 dB. The gain of amplifier 38 is varied by an AGC signal on a lead 39. By inserting most of the gain at the lower IF frequency, system stability is increased since feedback through parasitic capacitances, radiation, etc. is much less at 45 MHz than 100 330 MHz.

The output of amplifier 38 is coupled via lead 40 to a tank circuit 41, a synchronous detector 42 105 and the phase detector 43. Tank circuit 41 has a center frequency of approximately 45 MHz. Synchronous detector 42 has a second input coupled via a lead 44 to an oscillator 45. Oscillator 45 generates clock signals at a fixed frequency of 45 MHz on lead 44. The signals on lead 44 are in phase with the 45 MHz picture carrier on lead 40. 110 Detector 42 mixes the signals on leads 40 and 44 to generate output signals  $S_5(f)$  on a lead 46. Signal  $S_5(f)$  contains the selected television channel with the picture carrier at zero Hz and the sound carrier at 4.5 MHz. Lead 46 is then coupled to conventional television circuitry for separating the sound signal from the picture signals and for reproducing the sound and the picture from these 120 signals respectively in a conventional manner.

The synchronous clock signal on lead 44 is kept in phase with the picture carrier on lead 40 by means of the phase detector 43 operating in conjunction with oscillator 45. Phase detector 43 125 generates phase detection signals PD2 on lead 48 which indicate the phase difference between the picture carrier on lead 40 and the oscillator signal on lead 47. Signals PD2 maintain a 90° phase difference between the signals on leads 40 and 130 47. This phase difference is compensated for by

oscillator 45 which maintains a compensating 90° phase difference between the oscillator signals on leads 44 and 47.

To complete the phase locked loop, lead 48 couples to a loop filter 49, and the output of filter 49 couples to a summer 50 via leads 51. Summer 50 has a second input coupled to a controller 52 via a lead 53, and a third input coupled to a ramp oscillator 54 via lead 55. Controller 52 and oscillator 54 operate to provide a coarse voltage for selecting one channel from another. Channel selection switches 56 are coupled to controller 52 via leads 57. Switches 56 generate digital signals on leads 57 indicating the selected channel. Controller 52 contains a digital to analog converter which generates a coarse channel selection voltage on lead 53 in response to the digital signals. The signals on lead 53 are summed with the coarse signals on leads 51 and 55 to thereby provide a loop which is phase locked to the picture carrier of the selected channel. The output of summer 50 is coupled to VHF voltage controlled oscillator 22 via leads 58. Oscillator 22 generates LO signals on lead 23 of a frequency ranging from 385 MHz to 541 MHz in response to the phase detection signals on leads 58 thereby completing the loop.

The UHF—RF section of the FIGURE 1 channel selector begins with UHF antenna 59. Antenna 59 is coupled to a high pass filter 60 via a lead 61. Filter 60 has a fixed 3 dB cutoff frequency of approximately 380 MHz. The output of filter 60 couples to the input of an RF amplifier 62 via a lead 63. Amplifier 62 also has an AGC input which is connected to receive AGC signals on lead 19. The maximum gain of amplifier 62 is 4 dB, and its noise figure is also approximately 4 dB. A low pass filter 65 has its input coupled to the output of amplifier 62. Filter 65 has a fixed 3 dB cutoff frequency of approximately 936 MHz. Thus, filter 65 in combination with filter 60, pass the entire UHF band and reject other frequencies.

A mixer 67 receives the UHF band of signals from filter 65 via a lead 66. Mixer 67 simultaneously receives mixing signals of a selectable frequency from a UHF voltage controlled oscillator 68. These selectable frequencies range from approximately 801 MHz to 1215 MHz. The particular frequency at any time instant is generated in response to channel selection switches 56 so as to frequency shift the selected channel to the predetermined high IF.

The overall operation of the above described FIGURE 1 structure is as follows. Antennas 10 and 59 receive radiated electromagnetic signals which include the VHF and UHF frequency spectrum. The signals received by antenna 10 are applied to non-tuned filters 12 and 13 which respectively pass the entire low VHF and high VHF frequency spectrum. Similarly, the signals received by antenna 59 are applied to non-tuned filters 60 and 65 which pass the entire UHF frequency spectrum. Switch 15 and 25 select one of these three frequency spectrums in response to logic signals from the channel selection switches 56.

MESFET mixers 20 or 67 then frequency shift the selected frequency spectrum to a predetermined IF in the 300 MHz—400 MHz range. Mixer 20 frequency shifts VHF signals, whereas mixer 67 frequency shifts UHF signals. Both mixers have a large dynamic range over which their output is an almost perfect product of their inputs. As a result, the system has improved performance. For example, mixers 20 and 67 can handle >+6 dBm interfering signal levels on their output with less than 1% cross-modulation distortion.

Switch 25 then couples one of the mixers to the input of SWD filter 28. Filter 28 greatly attenuates signals outside the selected channel. In particular, the stopband of filter 28 is notched such that the lower adjacent sound carrier and upper adjacent picture carrier are attenuated by more than 65 dB. All other out of band signals are attenuated by at least 55 dB. Conversely, in band insertion loss of filter 28 is only 3.5 dB.

Output signals from filter 28 are sent to amplifier 29—which is the first high gain component of the system. Amplifier 29 has a maximum gain of 30 dB. In comparison, the total gain of the system before amplifier 29 is less than 10 dB. As a result of the low RF—IF gain, intermodulation distortion and cross modulation distortion is decreased. Further, system stability is improved since high frequency feedback due to parasitic capacitance, radiation, etc. is avoided. At the same time, low system noise figure is achieved by circuit elements which individually have a low noise figure in combination with a sufficiently high gain.

The low gain RF—IF section also makes feasible integration of all of the channel selectors, except the fixed filters, on a single semiconductor chip. An outline of such a chip is designated by the dashed line 69 in FIGURE 1. The process for fabricating the chip includes a combination of step presently well known for constructing MESFET devices and bipolar devices. A second chip is utilized to construct SWD filter 28 and SWD resonator 36. The fixed filters 12, 13, 60 and 65 are constructed of discrete components.

Signals in the selected channel at the output of amplifier 29 are frequency shifted to 45 MHz by mixer 32. Then they are further amplified to -10 dB, by amplifier 38. The selected channel video signals are then reduced to baseband by synchronous detector 42; while the sound carrier of the selected channel is shifted to 4.5 MHz. A 4.5 MHz trap 70 removes the sound from the video signals, and a low pass filter 71 removes all signals except the video of the selected channel. The video signals at the output of filter 71 are sent via lead 72 to video processing circuitry, while the audio signals at 4.5 MHz on lead 46 are sent to audio processing circuitry. This audio-video circuitry is described infra in conjunction with FIGURE 20.

Referring now to FIGURES 2a—2e, there is illustrated a set of frequency diagrams of signals  $S_1(f)$ — $S_6(f)$ . In FIGURE 2a, the low VHF band is

shown generally at 75a, the high VHF band is shown generally at 75b, and the UHF band is shown at 75c. Each of the bands is comprised of a plurality of channels; and each channel has a

5 frequency spectrum which is assigned as illustrated in detail at 76. The frequency allocation and type of modulation of signals within each channel is a well known standard that is fixed by the FCC. FIGURE 2b is an exemplary frequency  
10 diagram of signal  $S_2(f)$ . In the example illustrated, signal  $S_2(f)$  contains channels in the low VHF spectrum. The selected channel is near 330 MHz. The frequency of the LO signal on lead 23 minus the frequency of the picture carrier from the  
15 selected channel equals 330 MHz. Since the mixing frequency is higher than the picture carrier, the frequency spectrum at the output of mixer 20 is inverted from the input frequency spectrum as shown at 77.

20 FIGURE 2c illustrates the frequency spectrum of signal  $S_3(f)$ . Signal  $S_3(f)$  is the output of the channel selecting filter 28. Thus it basically contains only frequencies within the selected channel. Signal  $S_3(f)$  is then amplified and  
25 frequency shifted down by 285 MHz. The result is signal  $S_4(f)$  as illustrated in FIGURE 2d.

Signal  $S_4(f)$  is further amplified, and then synchronously detected by detector 42. These operations produce signal  $S_5(f)$  as illustrated in  
30 FIGURE 2e. Note that the mixing action of synchronous detector 42 again inverts the frequency spectrum of the selected channel. Thus the picture carrier of the selected channel is 0 Hz, and the sound carrier of the selected channel is at  
35 4.5 MHz as shown at 78.

FIGURE 3 is a timing diagram illustrating the operation of the channel selecting phase locked loop of FIGURE 1. As shown therein, signal PD4 on lead 58 is comprised of components PD1—PD3.  
40 Signal PD3 constitutes a coarse channel selection voltage which is produced by controller 52. Signals PD2 and PD1 provide the fine tuning for the phase locked loop. In the example of FIGURE 3, one particular channel is selected during a first time interval  $\Delta T1$ , while another channel is  
45 selected during a time interval  $\Delta T2$ . Signal PD3 provides the coarse voltage for channel selection. Signal PD1 compensates for any DC offset between signal PD3 and the desired voltage level.  
50 And signal PD2 provides a dynamic correction voltage to compensate for instantaneous phase or frequency differences between the signals on leads 40 and 44.

The magnitude of the signals of FIGURE 2 are illustrated in FIGURES 4a and 4b. FIGURE 4a illustrates the magnitude of signals in the desired channel, whereas FIGURE 4b illustrates the  
55 magnitude of interfering signals in a channel that is two channels removed. Curves 81—84

60 illustrate the magnitude of signals in the desired channel at various points in the system when the incoming signal strength is 0 dBm, -35 dBm, -55 dBm, and -85 dBm respectively. As these curves illustrate, gain is first added by amplifier  
65 38, then by amplifier 29, and finally by amplifier

17 as the input signal strength in the selected channel decreases. In particular, the RF section has no gain unless the input signal strength in the selected channel is less than -55 dBm. And the  
70 RF section reaches its maximum gain of +3 dBm when the input signal strength of the selected channel is between -55 dBm and -85 dBm.

As previously pointed out, the low gain RF section in combination with the MESFET RF  
75 amplifiers and MESFET RF mixer provides a system having superior channel discrimination capability. This is exemplified in FIGURE 4b by the relative signal strength of the selected and unselected channels. For example, curve 85 of  
80 FIGURE 4b illustrates the case where the input signal strength of the selected channel is -55 dBm and input signal strength two channels removed is +1 dBm. Similarly, curve 86 illustrates the case where the input signal strength in the  
85 selected channel -35 dBm and the input signal strength two channels removed is -2 dBm. The most stringent requirement for the receiver is when the first RF amplifier requires gain (i.e., when the signal strength of the desired channel is less  
90 than -55 dBm). This is because the added gain increases nonlinearities in the RF section and aggravates the cross modulation and intermodulation distortion. Thus, curve 85  
95 illustrates the most stringent condition for the system. Under the conditions of curve 85, RF amplifier 17 and mixer 20 must have cross modulation distortion and intermodulation  
100 distortion of less than 1%. And this requirement is met, since the MESFET designs herein described have less than 1% cross modulation distortion intermodulation distortion when their output  
signal level is less than +6 dBm.

After the selected channel has been shifted to 330 MHz, signals two channels removed from the  
105 selected channel are greatly attenuated. Mixer 20 has a tuned output which attenuates two channel removed signals by -4 DB. And SWD filter 28 attenuates all out of band signals by at least  
-53 DB. At the same time, mixer 20 adds 4 DB of gain to the desired signal. And filter 28 inserts  
110 only 3.5 DB of loss to signals in the selected channel.

The details of the various blocks of FIGURE 1 will now be described in conjunction with  
115 FIGURES 5—19. Referring first to FIGURE 5, a circuit diagram of bandpass filter 12 is therein illustrated. Basically, filter 12 is comprised of two series resonant LC circuits 91 and 92 and one  
120 parallel resonant LC circuit 93. Filter 13 is similarly structured.

A primary function of RF filters 12 and 13 is to pass one band of channels while rejecting image frequencies by an amount sufficient to eliminate perceptible picture interference. Since this system  
125 uses a 330 MHz IF, all image frequencies are 660 MHz above the frequency of the desired channel. Thus, the low VHF images are rejected by the three pole bandpass filter of FIGURE 5 by greater than 80 DB. In the system of FIGURE 1,  
130 just perceptible picture interference occurs when

image frequency signals are less than 36 DB below the level of the desired signal at the filter output. Thus, for example, the filter of FIGURE 5 provides adequate image frequency rejection when the desired picture signal level is at -55 DBM and the image frequency level is at -11 DBM. Image frequencies for the low VHF and the high VHF spectrum lie within the UHF spectrum, and the level of UHF signal at the input of the VHF antenna can normally be expected to be less than -11 DBM.

FIGURES 5b and 5c are circuit diagrams of a high pass filter and a low pass filter suitable for use by the UHF radio frequency section of FIGURE 1. All of the UHF images fall outside of the TV band. The first image falls at approximately 1130 MHZ and the last image falls at approximately 1545 MHZ. These frequencies are allocated for aircraft navigation, with the TACAN system having the highest power output. But TACAN power output is only 5 KW with a  $1.8 \times 10^{-3}$  to 1 duty cycle. And thus the TACAN signal is 50 DB lower than that transmitted by a 1 MW TV transmitter. Therefore, the filters of FIGURES 5b and 5c provide adequate rejection of image signals for the UHF band.

FIGURE 6 is a detailed circuit diagram of switch 15. One portion is basically comprised of a diode 101 connecting leads 14 and 18, and an RLC bias network 102 having a control input 103. A DC voltage control signal SELLOVHF is applied to lead 103 for selectively turning diode 101 on or off to thereby select or deselect the low VHF signals on lead 14. Another portion identical to the one described above coupled lead 18 to lead 16, and is utilized to select and deselect the high VHF channels.

Referring next to FIGURES 7 and 8, there is illustrated a detailed circuit diagram of RF amplifier 17 and mixer 20, respectively. Basically, amplifier 17 is comprised of a dual gate MESFET transistor 111 having a source coupled to a bias resistor and coupling capacitor 112, and a drain coupled to an L—C bandpass circuit 113. The gain of transistor 111 is varied about the levels indicated in FIGURE 4a by an automatic gain control signal AGCRF. Signal AGCRF coupled to a gate of transistor 111 through a voltage dividing network 114.

Similarly, mixer 20 is comprised of a single gate MESFET transistor 121 having a source coupled to a bias resistor and coupling capacitor 122, and a drain coupled to an L—C bandpass circuit 123. Circuit 123 has a center frequency of 330 MHZ. The mixing signals from VHF VCO 22 are coupled to the gate of transistor 121 via an RC circuit 124.

It should be emphasized that the Schottky barrier gate structure of the MESFET transistors of amplifier 17 and mixer 20 yield significant performance improvements over other known devices. Narrow gate depletion mode MOSFET devices have a high frequency response, but they approximate square-law transfer characteristics over only a very narrow range of gate bias. Since departure from square-law operation results in

cross modulation and intermodulation distortion, the devices are restricted to a small dynamic range. In comparison, the MESFET devices 111 and 121 have nearly ideal square-law characteristics over the entire operating range indicated in FIGURE 4a. JFET devices also have a good square-law transfer characteristic, but their high frequency performance is greatly reduced because of parasitic capacitance and process difficulties that limit their usable geometries.

Referring now to FIGURE 9a, there is illustrated a photograph of a completed MESFET device suitable for use as mixer 20. The MESFET of FIGURE 9a has a closed gate 131. Gate 131 is approximately 80 mils in length. The gate metal is approximately 0.3 mils wide, while the Schottky barrier gate in contact with the gate metal is approximately 0.15 mils wide. The source consists of five fingers 132—136 having lengths of 32.7 mils 4.1 mils, 4.1 mils, 7.7 mils and 12.1 mils respectively. The width of these fingers is approximately 0.3 mils. The drain consists of fingers 137—140.

FIGURE 9b is a greatly enlarged cross-sectional view taken along lines A—A of FIGURE 9a. The MESFET is constructed on a silicon substrate 140 having a P-type impurity. The conductivity of substrate 140 is approximately 50 ohm centimeter. Each of the source electrodes 132—136 couples to an N+ doped region 142—146 respectively. These doped regions have a conductivity of approximately 0.005 ohm centimeter. The doped regions extend beyond their corresponding electrodes by approximately 0.3 mils and are separated from the spaced apart gate electrode by approximately 0.15 mils. Similarly, the metal electrodes 137—140 which form the drain electrodes are coupled to underlying N+ doped regions 147—150, respectively. The conductivity and geometry of the drain doped regions is similar to that of the source doped regions.

FIGURE 9c is a greatly enlarged cross sectional view of one source drain pair within a dual gate MESFET device suitable for use with amplifier 17. The entire device is constructed similar to that of FIGURE 9a, with the modification that two gates are interleaved between the source and drain electrodes. In FIGURE 9c, source electrode 132a and drain electrode 137a correspond to electrodes 132 and 137 of FIGURE 9a. Gate electrodes 131a and 131b occupy the space of electrode 131 in FIGURE 9a.

FIGURE 9d illustrates the I—V characteristics of the devices of FIGURE 9a, while FIGURE 9e illustrates their transconductance as a function of gate voltage. In an ideal square-law device, the drain current is proportional to the square of the gate voltage. And since transconductance equals the partial derivative of drain current with respect to gate voltage, the transconductance is directly proportional to gate voltage for ideal square-law operation. FIGURE 9e demonstrates such a linear relation between the transconductance and gate voltage for the MESFET device of FIGURE 9a.



Referring now to FIGURE 10, a circuit diagram of switch 25 is illustrated. Switch 25 is constructed identical to the previously described switch 15 of FIGURE 6. The signals on leads 24 and 26 are selectively coupled to the output lead 27 via DC control signals select VHF (SELVHF) and select UHF (SELVHF) respectively.

FIGURES 11a—11h illustrate the details of SWD filter 28. Filter 28 is comprised of a surface wave device chip 160 having an L—C input circuit 170, and an L—C output circuit 190 for impedance matching and phase shifting signals to and from SWD device 160. Leads 172—174 and 192—194 couple circuits 170 and 190 to SWD 160 as illustrated in FIGURE 11a.

Device 160 has a magnitude-frequency characteristic as illustrated in FIGURE 11b. In particular, device 160 attenuates signals which are 1.5 MHz above the picture carrier of the desired channel by at least 65 db. At that frequency, the sound carrier of the channel adjacent to the desired channel is present. It is important to greatly attenuate this sound carrier because it is translated into the video signals of the selected channel by synchronous detector 42. That is, the sound carrier at 46.5 MHz is translated to 1.5 MHz by detector 42. In the receiver of FIGURE 1, just perceptible picture interference occurs when the sound carrier at 46.5 MHz is passed through SWD filter 28 with a magnitude that is within 36 dB of the picture carrier at 45 MHz. Thus, SWD filter 28 with its greater than 65 dB adjacent channel rejection enables the receiver of FIGURE 1 to have good picture reception even though signals at the filter input in an adjacent channel are much larger than signals in the desired channel. For example, if the signal level of the desired channel is -55 DBM at the input of filter 28, then the 46.5 MHz sound carrier at the input of filter 28 can be as high as -26 dBm and the receiver of FIGURE 1 will meet the requirement of a -36 dB difference between the in band and out band signals at the output of filter 28. By comparison, prior art television receivers typically have perceptible picture interference when the adjacent channel sound carrier is -40 dBm.

FIGURES 11c and 11d illustrate the physical structure of one embodiment of SWD 160. Basically, device 160 is comprised of a piezoelectric substrate 161 which in a preferred embodiment is made of quartz. Quartz has a desirable feature in that the velocity of surface waves through quartz is practically independent of temperature. The dependence of velocity on temperature is of considerable importance since velocity effects the center frequency of the filter as described below.

Three electrically independent conductors 162—164 are disposed on substrate 161. Each conductor has corresponding finger electrodes 162a—164a which are disposed on substrate 161 in a comb like fashion. Fingers 162a—164a are equally spaced. The distance between two consecutive fingers on the same conductor is one

wavelength of the center frequency of the filter. The velocity of a surface wave in quartz is approximately 3,300 meters per second, and the center frequency of device 160 is approximately 330 MHz. Thus, the distance between two consecutive 162a fingers for example is approximately  $10 \times 10^{-6}$  meters.

Conductors 162—164 are coupled to the input circuitry 180 of FIGURE 11a via leads 172—174 respectively. Input circuitry 170 generates voltages on electrodes 162—164 which are  $120^\circ$  out of phase with each other. This phase relationship generates a unidirectional surface wave on substrate 161. That is, waves in the forward direction add constructively, while waves in the reverse direction add destructively. As a result, device 160 has a low insertion loss for signals in the passband. In particular, the loss through filter 160 is no more than 3.5 DB. United States patent 3,686,518 issued August 27, 1972 to Hartmann et al and assigned to Texas Instruments Incorporated includes additional structural details of unidirectional surface wave filter 160.

FIGURE 11d illustrates a method for shaping the impulse response of surface wave filter 160. The method therein illustrated is known as the finger withdrawal method. It involved removal of groups of fingers from selected portions of substrate 161. Basically, the amplitude of the impulse response in those regions from which the fingers are removed is reduced below the value which it would have if the fingers had not been removed. The method thus provides the capability to control the relative amplitude of the impulse response along the length of substrate 161. The desired impulse response is obtained by taking the inverse Fourier transfer of the frequency response of FIGURE 11b; and then fingers 162a—164a are selectively removed in accordance with the desired impulse response. Further details of the finger withdrawal method are contained in U. S. Patent No. 3,946,342 issued March 23, 1976 to Hartmann and assigned to Texas Instruments Incorporated.

FIGURES 11e—11h illustrate a method for determining the value of inductors 175—177 and capacitor 178 comprising input circuitry 170. As was previously described, one of the functions of circuit 170 is to generate voltages on leads 172—174 which are shifted in phase from each other by  $120^\circ$ . FIGURE 11e illustrates that this  $120^\circ$  phase shift can be achieved by a circuit 180 which produces a  $60^\circ$  phase lag between the voltage on lead 172 and the voltage on lead 173, in combination with a grounding of lead 174. This point is further illustrated by the phaser diagram of FIGURE 11f.

A circuit for producing a  $60^\circ$  phase lag is illustrated in FIGURE 11g. The circuit consists of a pi shaped R—L—C network consisting of a capacitor 181, and inductor 182, a capacitor 183, and a resistor 184. Included in FIGURE 11g are two equations relating the angle of phase lag between leads 172 and 173 in terms of

components 181—184. In the case at hand, the angle of phase is  $60^\circ$ , and resistor 184 is the resistance between the electrodes 162 and 163 divided by 2. Thus, utilizing the equations of

FIGURE 11g, values for  $|X_i|$  and  $|X_c|$  can be calculated.

Impedance 183 is physically implemented by coupling inductor 175 across leads 173 and 174; and impedance 182 is physically implemented by coupling inductor 176 across leads 172 and 173 as illustrated in FIGURE 11h. The parallel combination of inductor 175 and the capacitance between leads 173 and 174 due to the SWD electrodes is chosen to equal impedance 183. Similarly, the parallel combination of inductor 176 and the capacitance across leads 172 and 173 due to the SWD electrodes is chosen to equal impedance 182. Inductor 175 may typically equal 30 nanohenries, while inductor 182 may typically equal 35 nanohenries as an example.

Inductor 177 is then added between leads 172 and 174 while capacitor 178 is added between leads 172 and 29 so as to match the impedance between leads 172 and 174. Typically, inductor 177 is approximately 25 nanohenries, and capacitor 174 is 10 picofarads.

To this point, the discussion with reference to FIGURES 11a—11h has concentrated primarily on the structure of input circuitry 170 and the input transducer of SWD device 160. It will be understood however, that surface wave device 160 also has an output transducer on substrate 161 of a construction similar to that of the input transducer. Also, output circuitry 190 of FIGURE 11a is constructed similar to input circuitry 170.

Referring next to FIGURES 12a and 12b, a circuit diagram of RF amplifier 29 is therein illustrated. Amplifier 29 is comprised of stages 200 and 201. Stage 200 includes a single bipolar transistor 202 as its amplifying element, whereas stage 201 includes several DC coupled bipolar transistors in an integrated circuit 203 as its amplifying element. Circuit 203 is indicated in FIGURE 12a as a single circuit element, and is shown in detail in FIGURE 12b.

Amplifier 29 provides a maximum gain of 30 DB to signals on its input lead 30. A small portion of the gain is provided by stage 200 which has a relatively good noise figure, whereas the remainder of the gain is provided by stage 201. AGC control signal AGCIF couples to stages 200 and 201 as indicated in FIGURE 12a through bias circuits 216 and 217. The magnitude of signal AGCIF varies so as to keep the output of amplifier 29 at approximately  $-26.5$  DBM. The variation of gain versus input signal strength for amplifier 29 was previously indicated in FIGURE 4a.

The output of amplifier 29 couples to mixer 32 which is illustrated in the circuit diagram of FIGURE 13. The basic mixing circuit element utilized therein is a bipolar transistor 220. Transistor 220 has an emitter 221 which is coupled to the output of amplifier 29. Similarly, transistor 220 has a base 223 which is coupled to SWD oscillator 35. Oscillator 35 generates mixing

signals of 285 MHZ on the base 223 of transistor 220. As a result, sum and difference frequencies are generated on the collector 225 of transistor 220. Collector 225 is coupled to an LC tank circuit 226 having a resonant frequency of about 45 MHZ. The output of tank circuit 226 is coupled via a tapped transformer 227 to lead 37 and signals  $S_n(f)$  are generated thereon.

Referring next to FIGURES 14a and 14b, a circuit diagram of oscillator 35 and a schematic diagram of acoustic surface wave resonator 36 are illustrated. Oscillator 35 includes a bipolar transistor 231 as the amplifying element. Transistor 231 has a grounded base 232, an emitter coupled via lead 233 to the input of resonator 36, and a collector coupled through a capacitor 234 to the output of resonator 36. An LC circuit 236 couples a DC supply voltage VDD to the collector of transistor 231 and also provides an output signal on lead 34.

Surface wave resonator 36 has a relatively high resonant frequency of 285 MHZ. Thus it is relatively small in size. Device size decreases as the resonant frequency increases. Typically, the SWD 36 of FIGURE 14b is only approximately 0.10 inches in length. SWD 36 also has good long term frequency stability. This is because the resonator has a large Q. typically its Q is greater than 15,000. Q is the ratio of energy stored to energy dissipated per cycle within the device.

SWD resonator 36 is comprised of a piezoelectric substrate 240 which in the preferred embodiment is made of quartz. Reflective grating structures 241 and 242 are disposed at opposite ends of substrate 240. These grating structures form discontinuities in the surface of 240 which reflect surface waves thereon. Gratings 241 and 242 may be comprised of grooves, or alternatively bars of gold or copper for an example. The bars are spaced apart by one half wavelength of the resonant frequency. Typically, 250 to 400 bars are contained within each of the grating structures 241 and 242. The Q of the resonator increases as the number of bars increases. Also, as previously pointed out, the velocity of the surface waves in quartz is relatively insensitive to temperature change. Thus, the resonant frequency of resonator 36 has low temperature drift. Typically, the resonant frequency varies less than 20 KHZ over temperature range 0—70C.

An input transducer 243 and an output transducer 244 are disposed on substrate 240 in the space between grating structures 241 and 242. Lead 233 couples to input transducer 243, and lead 235 couples to output transducer 244. Transducers 243 and 244 are comprised of a number of interleaved fingers which are placed at the peaks of the resonating standing wave that is set up by reflective grating structures 241 and 242. Typically, 60 fingers are on each transducer. Further details of resonator 36 are included in U.S. Patent 3,886,504 issued to Hartmann et al on May 27, 1975 and assigned to Texas Instruments Incorporated.

FIGURE 15 is a circuit diagram of amplifier 38.

Amplifier 38 is basically comprised of a circuit 250 which was previously illustrated in detail in FIGURE 12b. Nodes A—G of circuit 250 as illustrated in FIGURE 15 correspond to the node A—G as illustrated in FIGURE 12b. Signals from mixer 32 couple to the input of circuit 250 through a capacitor 251. The gain of circuit 250 is automatically adjusted by a gain control signal AGCIF. Signal AGCIF is coupled to node C through an RLC circuit 252. The output of circuit 250 is coupled to lead 40 through an LC tank circuit 253.

FIGURES 16—19 are detailed circuit diagrams of the remaining portions of the receiver of FIGURE 1. The circuits utilize conventional components and are generally self-explanatory to those with ordinary skill in the art. Synchronous detector 42 is illustrated in FIGURE 16. Detector 42 is essentially comprised of a commercially available chip MC 1596. Chip MC 1596 is described in the Linear Integrated Circuits Catalogue on pages 8—404 to 8—414 of Motorola's Semiconductor Data Library, Volume 6, Series, 1975. Details of the circuit are given on page 8—411 in FIGURE 23 of the cited reference. Chip MC 1596 is appropriately biased at each of its inputs and outputs by RLC circuits 261—269 as illustrated in FIGURE 16. The biasing required by the component is also described in the cited reference.

Oscillator 45 illustrated in FIGURE 17. Oscillator 45 has a MESFET transistor 270 as the amplifying element, and frequency determining L—C feedback networks 271 and 272. Two separate output signals are provided by oscillator 45. One of the output signals is generated on lead 47 and the other signal is generated on lead 44. Leads 44 and 47 are separated by an RLC phase shifting network 273 which generates approximately a 90° phase difference between the two signals. Phase shifting network 273 insures that the picture carrier on lead 40 is in phase with the oscillator signal on lead 44. The phase detecting circuit 43, as illustrated in FIGURE 18, generates phase detection signals PD1 and PD2 which lock the oscillator signal on lead 47 90° out of phase with the picture carrier on lead 40. Circuit 273 reinserts this 90° phase shift.

The phase detector 43 of FIGURE 18 also utilizes chip MC 1596 as was utilized in sync detector 42. Bias networks 281—287 are applied to chip MC 1596 to achieve the phase detecting function. Ramp generator 54 and loop filter 49 couple to outputs of chip MC 1596 as illustrated in FIGURE 18. The combination generates phase detecting signals PD1 and PD2 on leads 51.

FIGURE 19 illustrates a circuit diagram of VHF—VCO 22. VHF—VCO 22 utilizes phase signals PD1 and PD2 in combination with a third signal PD3 to generate the selectable frequency LO signals on lead 23. Signal PD3 is a multilevel analog signal which provides a coarse voltage level of a unique value for each channel to be selected. Signal PD3 is generated by controller 52 in response to manually operated channel

selection switches 56 as is previously described in

conjunction with FIGURE 1. Signals PD1—PD3 are coupled across a varactor diode 290 through summer 50. Diode 290 in combination with capacitors 291 and a micro strip 292 forms the frequency determining circuit of VHF—VCO 22. Signal amplification within VCO 22 is provided by a bipolar transistor 293. Transistor 293 is selectively enabled or disabled by a control signal "enable VHF" (ENVHF). Signal ENVHF couples to the base of transistor 293 through a resistor 294 and to the collector of transistor 293 through an inductor 295. It is selectively energized in response to the position of the channel selection switches 56.

A complete television receiver which incorporates the channel selector of FIGURE 1 is illustrated in block diagram form in FIGURE 20. The channel selector has input leads 11 and 61 for receiving VHF and UHF television signals as previously described. The channel selector also has input leads 53 for receiving coarse analog voltages indicating the selected channel. The RF section of the channel selector frequency shifts the selected channel to approximately 330 MHz, while the IF section of the channel selector filters the channel at 330 MHz and frequency shifts the filtered channel to baseband.

Lead 46 is the audio output of the channel selector. As previously described, the sound carrier of the selected channel is generated on lead 46 at 4.5 MHz. Lead 46 is coupled to the input of an audio demodulator 301. Demodulator 301 generates signals on a lead 302 with an amplitude that is proportional to the frequency of the frequency modulated signals on lead 46. This frequency demodulation process may be implemented by a variety of circuits that are well known in the art. The demodulated signals on lead 302 couple to the input of a speaker 303 where they are electromechanically converted to audible sounds.

Lead 72 is the composite video output of the channel selector. That is, signals on lead 72 include frame synchronizing information and video information of the selected channel. Lead 72 couples to the input of a video processing unit 304. Video processor 304 separates the picture signals from the frame synchronizing signals. The picture signals are generated on a lead 305 which couples to the electron gun input of a picture tube 306. The frame synchronizing signals are generated on a lead 307 which couples to the input of a drive circuit 308. Drive circuit 308 generates horizontal and vertical synchronizing signals on a lead 309 which couples to electron beam deflection circuitry 310 of picture tube 306. Drive circuit 308 also generates horizontal synchronizing signals on a lead 311 which couples to an input of picture tube high voltage generator 312. Additionally, drive circuit 308 generates synchronizing signals on lead 73 which couples to the AGC circuitry 74 of the channel selector.

Television receiver components 301—312 have been described in detail in many prior art publications. See for example the Fundamentals of

Display System Design by Sol Sherr, 1970, published by Wiley-Interscience. A bibliography on pages 445—469 of the cited reference also includes many additional references.

5 FIGURE 21 is a block diagram of a second embodiment of a channel selector constructed according to the invention. A significant portion of this second embodiment is similar in construction to that of the FIGURE 1 embodiment. The similar  
10 portions are indicated by the identifying reference numerals.

One structural difference of the second embodiment is that it has only one VHF filter. That is, signals on VHF antenna 10 are coupled to a  
15 local oscillator mixer 320 through a fixed filter 321 which passes the entire VHF band of frequencies. A second difference is that the embodiment of FIGURE 21 contains no RF amplifier. As a result, the system has improved  
20 intermodulation distortion and cross modulation distortion but has increased noise figure. Still another difference is that the FIGURE 21 embodiment contains only one RF MESFET mixer. A two by one switch 322 is provided having one  
25 input coupled to receive VHF signals on a lead 323 and a second input coupled to receive UHF signals on a lead 324. The output of switch 322 couples via a lead 325 to MESFET 320.

The embodiment of FIGURE 21 also includes a  
30 different means for generating the coarse channel selection voltages on leads 53. As FIGURE 21 illustrates, controller 52 is comprised of a phase locked loop. The loop receives reference signals of a fixed frequency from a circuit 331, and  
35 simultaneously receives feedback signals from the LO VCO. The LO VCO signals are sent through a variable counter 332. Counter 332 divides by a number which is selectable via logic signals on leads 333. The signals on leads 333 are  
40 generated by a logic circuit 334 in response to logic signals received from the channel selection switches 56. A phase detector 335 compares the output signals of variable counter 332 to the reference signals, and generates phase detection  
45 signals for the LO VCO. thus, a relatively high local oscillator frequency is generated when counter 332 is selected to divide by a relatively large number and vice versa.

Various embodiments of the invention have  
50 now been described in detail. However, many changes and modifications can be made to the above details without departing from the nature and spirit of the invention. For example, the IF frequency of the mixer output is not restricted to  
55 330 MHz. Other IF frequencies in the range of 300—400 MHz may be employed. As another example, a bipolar RF amplifier may be substituted for the MESFET RF amplifier. This is because the mixer introduces cross modulation distortion and  
60 intermodulation distortion into the receiver to a much more significant degree than does the linear RF amplifier. Thus, utilization of a MESFET mixer yields a receiver having greatly improved third order distortion even though the RF amplifier is  
65 bipolar. As another example, the surface wave

device resonator utilized to generate 285 MHz mixing signals may be comprised of a single transducer as opposed to a dual transducer. In a single transducer resonator, lead 233 couples to one set of electrodes on the transducer while lead  
70 235 couples to the other set of electrodes. The single transducer is configured similar to transducer 243. As still another example, the channel selector of FIGURE 1 or FIGURE 21 may be readily adapted for use in systems other than  
75 television receivers. The channel selector has application wherever one channel of frequencies is desired to be selected from a plurality of nonoverlapping frequency channels. The information contained in the channels need not be  
80 television signals. Therefore, since it is obvious that many changes and modifications can be made to the above details without departing from the nature and spirit of the invention, it is understood that the invention is not limited to said  
85 details except as set forth in the appended claims.

#### CLAIMS

1. In a channel selector for a television receiver including a radio frequency section and an  
90 intermediate frequency section, the combination comprising:

fixed bandpass filter means disposed in the radio frequency section, said radio frequency section being characterized by an absence of any  
95 tuners therein, said fixed bandpass filter having at least one unalterable predetermined frequency passband for receiving radio frequency signals representative of a plurality of television channels and for filtering at least one fixed frequency  
100 spectrum of television channels from the received signal; and

at least one mixing means connected to the output of said fixed bandpass filter means, said mixing means including a metal semiconductor  
105 field effect transistor and having first and second inputs coupled to simultaneously receive said mixed frequency spectrum of television channels from said fixed bandpass filter means and mixing signals of a selected intermediate frequency for  
110 frequency shifting the selected frequency channel of said fixed frequency spectrum of television channels to a high intermediate frequency substantially greater than 45 MHz.

2. In a channel selector as set forth in Claim 1, wherein the frequency magnitude which equals  
115 twice the high intermediate frequency produced from said mixing means plus the lowest frequency of said fixed frequency spectrum is outside the passband of said fixed bandpass filter means.

3. In a channel selector as set forth in Claim 1, wherein the high intermediate frequency produced  
120 from said mixing means is between 300 MHz and 400 MHz.

4. In a channel selector as set forth in Claim 1, wherein said one fixed frequency spectrum of  
125 television channels is approximately 55—87 MHz.

5. In a channel selector as set forth in Claim 1,

wherein said one fixed frequency spectrum of television channels is approximately 175—215 MHZ.

6. In a channel selector as set forth in Claim 1, wherein said one fixed frequency spectrum of television channels is approximately 55—215 MHZ.

7. In a channel selector as set forth in Claim 1, wherein said one fixed frequency spectrum of television channels is approximately 470—890 MHZ.

8. In a channel selector as set forth in Claim 1, further including acoustic surface wave filter means having an input connected to the output of said mixing means for filtering said selected frequency channel at said high intermediate frequency so as to pass said selected frequency channel.

9. In a channel selector as set forth in Claim 8, wherein said acoustic surface wave filter means includes a substrate of piezoelectric material having a coefficient of coupling substantially less than that of lithium niobate.

10. In a channel selector as set forth in Claim 9, wherein said substrate of said acoustic surface wave filter means is made of quartz.

11. In a channel selector as set forth in Claim 8, wherein said acoustic surface wave filter means includes a relatively small substrate of piezoelectric material having a plurality of spaced apart electrodes disposed thereon, and the space between successive electrodes being inversely proportional to the high intermediate frequency produced from said mixing means.

12. In a channel selector as set forth in Claim 8, further including mixing means disposed in the intermediate frequency section and having first and second inputs coupled to simultaneously receive the filtered selected frequency channel at said high intermediate frequency from the output of said acoustic surface wave filter means and mixing signals of a predetermined fixed frequency for frequency shifting said filtered selected frequency channel at said high intermediate frequency to a substantially lower second intermediate frequency.

13. In a channel selector for a television receiver including a radio frequency section and an intermediate frequency section the combination comprising:

a plurality of fixed bandpass filter means disposed in the radio frequency section, said radio frequency section being characterized by an absence of any tuners therein, said plurality of fixed bandpass filter means including first and second fixed bandpass filters having respective first and second unalterable predetermined frequency passbands for receiving radio frequency signals in the low and the high ranges within the very high frequency range and representative of respective groups of television channels and for filtering first and second fixed frequency spectrums of television channels therefrom, and a third fixed bandpass filter means having a respective unalterable predetermined frequency passband for

receiving radio frequency signals representative of a group of television channels in the ultra high frequency range and for filtering a third fixed frequency spectrum of television channels therefrom:

first switching means connected to the outputs of said first and second fixed bandpass filters;

first and second mixing means, each of said mixing means including a metal semiconductor field effect transistor and having first and second inputs coupled to simultaneously receive radio frequency signals representative of a plurality of frequency channels and mixing signals of a selectable intermediate frequency for frequency shifting the selected frequency channel to a high intermediate frequency, said first mixing means being connected to the output of said first switching means for alternately receiving at its first input one of said first and second fixed frequency spectrums of television channels from said first and second fixed bandpass filters depending upon which of said fixed bandpass filters is interconnected thereto via said first switching means, said second mixing means having its first input coupled to receive said third fixed frequency spectrum of television channels from said third fixed bandpass filter means; and

second switching means connected to the outputs of said first and second mixing means, said second switching means being operable to alternately transmit the outputs of said first and second mixing means for providing a selected one of said first, second and third fixed frequency spectrums of television channels including a frequency-shifted selected frequency channel to a high intermediate frequency substantially greater than 45 MHZ.

14. In a channel selector as set forth in Claim 13, further including acoustic surface wave filter means having an input connected to the output of said second switching means, said second switching means being operable to alternately interconnect the outputs of said first and second mixing means to said acoustic surface wave filter means such that said acoustic surface wave filter means is interconnected via said second switching means

15. In a channel selector as set forth in Claim 14, further including mixing means disposed in the intermediate frequency section and having first and second inputs coupled to simultaneously receive the filtered selected frequency channel at said high intermediate frequency from said acoustic surface wave filter means and mixing signals of a predetermined fixed frequency for frequency shifting said filtered selected frequency channel at said high intermediate frequency to a substantially lower second intermediate frequency.

16. In a channel selector for a television receiver including a radio frequency section and an intermediate frequency section, the combination comprising:

first and second fixed bandpass filter means disposed in the radio frequency section, said radio

frequency section being characterized by an absence of any tuners therein, said first fixed bandpass filter means having a first unalterable predetermined frequency passband for receiving  
 5 radio frequency signals representative of a plurality of television channels and for filtering a first fixed frequency spectrum of television channels therefrom, said second fixed bandpass filter means having a second unalterable predetermined  
 10 frequency passband for receiving radio frequency signals representative of a second plurality of television channels and for filtering a second fixed frequency spectrum of television channels therefrom;

15 switching means connected to the outputs of said first and second fixed bandpass filter means; mixing means connected to the output of said

switching means, said mixing means including a metal semiconductor field effect transistor and  
 20 having first and second inputs coupled to simultaneously receive one of said first and second fixed frequency spectrums of television channels from said first and second fixed bandpass filter means and mixing signals of a selected  
 25 intermediate frequency for frequency shifting the selected frequency channel of said one fixed frequency spectrum of television channels to a high intermediate frequency substantially greater than 45 MHz; and

30 said switching means being operable to alternately interconnect the outputs of said first and second fixed bandpass filter means to said mixing means for transmitting the selected one of said first and second fixed frequency spectrums of  
 35 television channels to the first input of said mixing means.

17. In a channel selector as set forth in Claim 16, wherein the respective first and second predetermined frequency passbands of said first  
 40 and second fixed bandpass filter means correspond to the low and high ranges within the very high frequency range.

18. In a channel selector as set forth in Claim 17, further including acoustic surface wave filter  
 45 means having an input connected to the output of

said mixing means for filtering said selected frequency channel at the high intermediate frequency so as to pass only the selected frequency channel at said high intermediate  
 50 frequency.

19. In a channel selector as set forth in Claim 18, further including mixing means disposed in the intermediate frequency section and having first and second inputs coupled to simultaneously  
 55 receive the filtered selected frequency channel at said high intermediate frequency from said acoustic surface wave filter means and mixing signals of a predetermined fixed frequency for frequency shifting said filtered selected frequency  
 60 channel at said high intermediate frequency to a substantially lower second intermediate frequency.

20. In a channel selector as set forth in Claim 16, wherein the first predetermined frequency passband of said first fixed bandpass filter means includes the entire very high frequency range, and the second predetermined frequency passband of  
 65 said second fixed filter means includes the entire ultra high frequency range.

21. In a channel selector as set forth in Claim 20, further including acoustic surface wave filter means having an input connected to the output of  
 70 said mixing means for filtering said selected frequency channel at the high intermediate frequency so as to pass only the selected frequency channel at said high intermediate  
 75 frequency.

22. In a channel selector as set forth in Claim 21, further including mixing means disposed in the intermediate frequency section and having first and second inputs coupled to simultaneously  
 80 receive the filtered selected frequency channel at said high intermediate frequency from said acoustic surface wave filter means and mixing signals of a predetermined fixed frequency for frequency shifting said filtered selected frequency  
 85 channel at said high intermediate frequency to a substantially lower second intermediate frequency.